

# Storm INT e90-29 Lady Touring

MATT DARK BLUE/SILVER/PINK

E-TOUR



## E-BIKE

<b>E-BIKE SYSTEM</b>	SPORT DRIVE - Middle Drive Unit
<b>DRIVE UNIT</b>	SPORT DRIVE MD250S, 36V, 250W, 85Nm, torque/rotation sensor
<b>BATERIA</b>	SPORT DRIVE, 36V, 504Wh, in-frame mount
<b>WYŚWIETLACZ</b>	SPORT DRIVE Color display with USB port
<b>ŁADOWARKA</b>	SPORT DRIVE standard charger, 36V/4A, charging time up to 4 hours
<b>MAX SUPPORT SPEED</b>	25 km/h
<b>CYKLE ŁADOWANIA</b>	1000/80% of original capacity
<b>DISTANCE RANGE</b>	100 km (1st level of support)

## FRAMESET

<b>KOLOR</b>	Matte Dark Blue/Silver/Pink
<b>RAMA</b>	Alloy Al-6061 T6 Custom MONO tubing, Smooth Welding, Fun Ride Geometry, Lady 29er, Sport Drive MID Motor, 2nd Gen. Battery Integration, OLD 135x9, Disc Brake Post Mount, Fender&Kickstand Ready Dropout, Replaceable RD Hanger, Inner Cable Routing
<b>STERY</b>	FSA Orbit 1.5E No.57B, Zero Stack, 1-1/8"-1.5"
<b>WIDELEC</b>	SR SR Suntour Mobie25 RLR, Tapered, Coil, QR Type, Remote Lockout, 100mm travel
<b>ROZMIAR</b>	17.0"(M), 19.0"(L)

## DRIVETRAIN

<b>BIEGI</b>	1x9
<b>MANETKA</b>	SHIMANO ALTUS SL-M2010-9R RapidFire Plus, 9-speed
<b>PRZERZUTKA TYŁ</b>	SHIMANO ALTUS RD-M2000 Shadow
<b>MECHANIZM KORBOWY</b>	Wheel Top ED2L, 38T
<b>KASETA</b>	SHIMANO CS-HG200-9, 11-36T
<b>ŁAŃCUCH</b>	KMC e9S
<b>PEDAŁY</b>	Marwi SP-827 SANDBLOCK Non/slip pedal

## COMPONENTS

<b>KIEROWNICA</b>	ONE1 Alloy, MTB AL-325BT, 6° upsweep, 9° backsweep, 25mm rise, 680mm, 31.8mm
<b>MOSTEK</b>	ONE1 TDS-C342 Alloy, 31.8xE45mm, +3°
<b>CHWYTY</b>	Velo VLG-1879D2, Ergo Grip
<b>HAMULCE (PRZÓD/TYŁ)</b>	SHIMANO BL-MT200/BR-MT200, 160/160 rotor, hydraulic disc brake
<b>SIODŁO</b>	WTB Koda Sport
<b>SZTYCA</b>	ONE1 Alloy, SPS 405, 30.9x350mm

## WHEELS

<b>PIASTA PRZÓD</b>	SHIMANO DEORE HB-M6010, 32H, CENTER LOCK, 15x100mm THRU Type AXLE
<b>PIASTA TYŁ</b>	SHIMANO ALIVIO FH-M4050, 32H, CENTER LOCK, M10x135mm, QR Type
<b>OBRĘCZE</b>	WTB SX19, 32H
<b>OPONY</b>	WTB Nineline Comp, 29x2.25", Reflective Tape
<b>SZPRYCHY</b>	Sapim Galvanized Black

## ACCESSORIES

<b>CHWYTY</b>	AXA Blueline 30
<b>CHWYTY</b>	Spanninga Pling

## WEIGHT

25.9 Kg (M size)

## GEOMETRY

FRAME SIZE	17.0" (M)	19.0" (L)
WHEEL SIZE	29"	29"
SEAT TUBE LENGTH (MM)	432	473
SEAT TUBE ANGLE (DEGREE)	74,5	74,5
EFFECTIVE TOP TUBE LENGTH (MM)	615	645
REACH (MM)	436	466
STACK HEIGHT (MM)	625	625
HEAD TUBE LENGTH (MM)	175	175
HEAD TUBE ANGLE (DEGREE)	67	67
CHAINSTAY LENGTH (MM)	480	480
BB DROP (MM)	35	35
WHEELBASE (MM)	1215	1245
HANDLEBAR WIDTH (MM)	680 - R25	680 - R25
STEM LENGTH (MM)	45	45
CRANK LENGTH (MM)	170	170
SEAT POST LENGTH (MM)	350	350

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.